


For information on L, L3, and L4 max, see page T143.



■ VDS403F • 8 x D



● first choice
○ alternate choice

		D1 diameter							
grade WU25PD TiAlN		mm	in	L4 max	L3	L5	L	LS	D
4144208	VDS403F03000	3,000	.1181	33	40	0,5	78	36	6
4144210	VDS403F03100	3,100	.1220	33	40	0,5	78	36	6
4144243	VDS403F03200	3,200	.1260	33	40	0,5	78	36	6
4144245	VDS403F03300	3,300	.1299	33	40	0,5	78	36	6
4144247	VDS403F03400	3,400	.1339	33	40	0,6	78	36	6
4144249	VDS403F03500	3,500	.1378	33	40	0,6	78	36	6
4144251	VDS403F03600	3,600	.1417	33	40	0,6	78	36	6
4144253	VDS403F03700	3,700	.1457	33	40	0,6	78	36	6
4144255	VDS403F03800	3,800	.1496	41	49	0,6	87	36	6
4144257	VDS403F03900	3,900	.1535	41	49	0,6	87	36	6
4144259	VDS403F04000	4,000	.1575	41	49	0,7	87	36	6
4144261	VDS403F04100	4,100	.1614	41	49	0,7	87	36	6
4144273	VDS403F04200	4,200	.1654	41	49	0,7	87	36	6
4144274	VDS403F04300	4,300	.1693	41	49	0,7	87	36	6
4144276	VDS403F04400	4,400	.1732	41	49	0,7	87	36	6
4144278	VDS403F04500	4,500	.1772	41	49	0,7	87	36	6
4144280	VDS403F04600	4,600	.1811	41	49	0,8	87	36	6
4144282	VDS403F04700	4,700	.1850	41	49	0,8	87	36	6
4144284	VDS403F04800	4,800	.1890	48	56	0,8	94	36	6
4144286	VDS403F04900	4,900	.1929	48	56	0,8	94	36	6
4144288	VDS403F05000	5,000	.1969	48	56	0,8	94	36	6
4144290	VDS403F05100	5,100	.2008	48	56	0,8	94	36	6
4144292	VDS403F05200	5,200	.2047	48	56	0,9	94	36	6
4144304	VDS403F05300	5,300	.2087	48	56	0,9	94	36	6

(continued)

Solid Carbide Drills