

■ TOP DRILL S+ • TDS504 • WU20PD™ • Through Coolant • Metric

Material Group													
		Cutting Speed — vc		Recommended Feed Rate (f) by Diameter									
		Range — m/min											
		min	—	max	Tool Diameter (mm)	3,0	4,0	6,0	8,0	10,0	12,0	16,0	20,0
P	1	90	—	180	mm/r	0,08–0,16	0,09–0,18	0,12–0,24	0,14–0,29	0,17–0,34	0,20–0,39	0,24–0,47	0,31–0,60
	2, 3, 4, 6, 7	80	—	120	mm/r	0,09–0,17	0,10–0,19	0,14–0,25	0,17–0,31	0,21–0,37	0,24–0,42	0,29–0,52	0,38–0,65
	5, 9, 10, 11	70	—	120	mm/r	0,08–0,17	0,09–0,19	0,13–0,25	0,16–0,31	0,19–0,37	0,21–0,42	0,26–0,52	0,32–0,65
	12, 13	50	—	80	mm/r	0,05–0,09	0,06–0,11	0,09–0,16	0,11–0,20	0,14–0,24	0,15–0,27	0,20–0,35	0,26–0,45
M	14,1	30	—	50	mm/r	0,04–0,07	0,05–0,09	0,08–0,11	0,09–0,12	0,10–0,14	0,12–0,16	0,14–0,18	0,16–0,20
	14,3	30	—	60	mm/r	0,04–0,08	0,06–0,10	0,08–0,12	0,09–0,14	0,10–0,16	0,12–0,18	0,14–0,20	0,16–0,22
	14.2, 14.4	30	—	50	mm/r	0,04–0,07	0,06–0,09	0,08–0,11	0,09–0,12	0,10–0,14	0,12–0,16	0,14–0,18	0,16–0,20
K	15, 16	100	—	210	mm/r	0,11–0,22	0,12–0,24	0,16–0,31	0,20–0,38	0,23–0,44	0,25–0,49	0,31–0,60	0,38–0,74
	17, 18, 19	130	—	160	mm/r	0,11–0,17	0,12–0,19	0,16–0,25	0,20–0,31	0,23–0,36	0,25–0,40	0,31–0,48	0,38–0,60
	20	100	—	170	mm/r	0,08–0,17	0,09–0,19	0,12–0,25	0,14–0,30	0,17–0,35	0,19–0,40	0,24–0,48	0,30–0,60

Metric

tolerance

nominal size range	D1 tolerance m7	D tolerance h6
>3–6	0,004/0,016	0,000/-0,008
>6–10	0,006/0,021	0,000/-0,009
>10–18	0,007/0,025	0,000/-0,011
>18–25,4	0,008/0,029	0,000/-0,013