

■ Straight Flute Holders • Long

long	D1		D1 max		L	L1	L4 max	LS	CSMS system size	seat size	CS	insert screw	Torx wrench
	mm	in	mm	in									
7SZTL	11,10	.437	12,90	.508	8.51	5.57	3.30	3.13	2	Z	8 - 32	56-1015	56-2026
7S0TL	12,93	.509	17,65	.695	9.88	6.94	4.60	3.13	2	0	8 - 32	56-1014	56-2017
7S1TL	17,53	.690	24,38	.960	12.60	8.91	6.36	3.88	3	1	1/4 - 20	56-1020	56-2028
7S2TL	24,41	.961	35,05	1.380	14.19	10.50	7.86	3.88	3	2	1/4 - 20	56-1018	56-2015
7S3TL	35,08	1.381	47,73	1.879	20.88	16.25	13.28	4.88	4	3	5/16-18	56-1585	56-2020
7S4TL	47,75	1.880	65,28	2.570	23.75	19.12	15.90	4.88	4	4	5/16-18	56-1585	56-2020
7S5TL	63,50	2.500	88,90	3.500	26.88	21.00	17.13	6.13	5	5	1/2 - 13	56-1025	56-2125
7S7TL	88,93	3.501	114,30	4.500	30.53	24.65	19.75	6.13	5	7	1/2 - 13	56-1025	56-2125

NOTE: CSMS = Morse taper size.

■ Straight Flute Holders • Extra Long

extra long	D1		D1 max		L	L1	L4 max	LS	CSMS system size	seat size	CS	insert screw	Torx wrench
	mm	in	mm	in									
7S0TE	12,93	.509	17,65	.695	12.93	10.00	7.65	3.13	2	0	8 - 32	56-1014	56-2017
7S0.5TE	15,47	.609	17,65	.695	12.93	9.80	7.60	3.13	2	—	8 - 32	56-1014	56-2017
7S2TE	24,41	.961	35,05	1.380	17.26	13.57	11.07	3.88	3	2	1/4 - 20	56-1018	56-2015

NOTE: CSMS = Morse taper size.