



Indexable Drills

Top Cut 4™ Inserts



- first choice
○ alternate choice

P	●	○	○	○
M	○	○	○	○
K	○	○	○	○
N	○	○	○	○
S	○	○	○	○
H	○	○	○	○

■ Top Cut 4 Drill • Periphery Inserts • V34

catalogue number	D	D1	W	S	RR	insert size	WPK10CH	WU25CH	WU40PH
TCF040204APV34	4,14	2,10	4,40	2,00	0,400	A	5541843	5541841	5541842
TCF050204BPV34	5,07	2,40	5,40	2,40	0,400	B	5542620	5542608	5542609
TCF070306CPV34	6,67	2,60	7,10	2,80	0,600	C	5542648	5542646	5542647
TCF080308DPV34	8,08	2,80	8,60	3,00	0,800	D	5538600	5538558	5538559
TCF100408EPV34	9,96	3,40	10,60	3,60	0,800	E	5538610	5538608	5538609
TCF120412FPV34	12,59	4,80	13,40	4,20	1,200	F	5542629	5542627	5542628
TCF150512GPV34	15,13	6,00	16,10	5,40	1,200	G	5542601	5542479	5542600
TCF180614HPV34	18,04	7,50	19,20	6,50	1,400	H	5542008	5542006	5542007

NOTE: For application-specific insert selection, please refer to the application data on pages V24–V35.

Geometry	Application
V34	First choice for machining steel, cast iron, and short chipping materials. Suitable for severe cutting conditions.
V36	First choice for stainless steel. Suitable for long chipping steel and where low power consumption is required.