


Shank Tolerance

D mm	tolerance h6
6	+0, -0,008
8-10	+0, -0,009
12-18	+0, -0,011
20-30	+0, -0,013


■ GTM21 • Through Coolant • Metric and Metric Fine


● first choice

○ alternate choice

 grade WU12PV
 TiCN

metric dimensions

order #	catalogue #	D1 size	D1	DCH	LTHD	LDCH	L	LS	D	cutting edges
4138514	GTM215001	M5X0.8	4,0	5,30	10,82	11,40	55	36	6,0	3
4138521	GTM215008	M6X0.75	5,0	6,30	12,40	12,97	62	36	8,0	3
4138515	GTM215002	M6X1	4,8	6,30	12,52	13,19	62	36	8,0	3
4138522	GTM215009	M8X1	6,7	8,30	16,53	17,23	74	40	10,0	3
4138516	GTM215003	M8X1.25	6,5	8,30	16,91	17,71	74	40	10,0	3
4138523	GTM215010	M10X1	8,7	10,30	20,55	21,23	80	45	12,0	3
4138524	GTM215011	M10X1.25	8,4	10,30	20,67	21,50	80	45	12,0	3
4138517	GTM215004	M10X1.5	8,2	10,30	20,29	21,22	80	45	12,0	3
4138525	GTM215012	M12X1	10,6	12,30	24,56	25,27	90	45	14,0	4
4138526	GTM215013	M12X1.25	10,4	12,30	24,43	25,24	90	45	14,0	4
4138527	GTM215014	M12X1.5	10,1	12,30	24,80	25,76	90	45	14,0	4
4138518	GTM215005	M12X1.75	9,9	12,30	25,42	26,48	90	45	14,0	4
4138528	GTM215015	M14X1.5	12,1	14,30	29,31	30,25	100	48	16,0	4
4138519	GTM215006	M14X2	11,6	14,30	29,05	30,24	100	48	16,0	4
4138529	GTM215016	M16X1.5	14,0	16,30	32,31	33,30	102	48	18,0	4
4138520	GTM215007	M16X2	13,6	16,30	33,05	34,24	102	48	18,0	4