

■ Carbide Taps • Metric

Material Group		 Through Holes					 Blind Holes				
				Range – m/min					Range – m/min		
		Tap Style	Grade	min	Starting Value	max	Tap Style	Grade	min	Starting Value	max
P	P0	GX32, GX38	GP4535	60	100	130	GX33, GX39	GP4535	50	70	90
	P1	GX32, GX38	GP4535	60	90	120	GX33, GX39	GP4535	40	60	80
	P2	GX32, GX38	GP4535	50	85	110	GX33, GX39	GP4535	40	60	80
	P3	GX32, GX38	GP4535	50	80	100	GX33, GX39	GP4535	40	60	80
K	K1	GX34, GX50	WK12PG	70	105	140	GX35, GX50	WK12PG	50	70	90
	K2	GX34, GX50	WK12PG	60	100	130	GX35, GX50	WK12PG	50	70	90
	K3	GX34, GX50	WK12PG	60	90	120	GX35, GX50	WK12PG	40	60	80
N	N2	GX46, GX48	WN14PG	80	120	160	GX47, GX49	WN14PG	60	80	100
	N3	GX46, GX48	WN14PG	60	100	130	GX47, GX49	WN14PG	50	70	90
	N4	GX46, GX48	WN14PG	60	90	120	GX47, GX49	WN14PG	40	60	80
H	H3	GX10	WH16PG	1,2	1,5	2,0	GX10	WH16PG	0,8	1,1	1,4
	H4	GX10	WH16PG	0,6	0,8	1,0	GX10	WH16PG	0,4	0,5	0,7