


**■ DIN 374**

| D1  | pitch   |         | D  | L   | metric dimensions |    |      |
|-----|---------|---------|----|-----|-------------------|----|------|
|     | minimum | maximum |    |     | L3*               | L5 | S10  |
| M8  | 0.2     | 0.75    | 6  | 80  | 18                | 8  | 4.9  |
| M8  | –       | 1       | 6  | 90  | 22                | 8  | 4.9  |
| M9  | 0.2     | 0.75    | 7  | 80  | 18                | 8  | 5.5  |
| M9  | –       | 1       | 7  | 90  | 22                | 8  | 5.5  |
| M10 | 0.2     | 1       | 7  | 90  | 20                | 8  | 5.5  |
| M10 | –       | 1.25    | 7  | 100 | 24                | 8  | 5.5  |
| M11 | 0.35    | 1       | 8  | 90  | 20                | 9  | 6.2  |
| M12 | 0.35    | 1.5     | 9  | 100 | 22                | 10 | 7    |
| M14 | 0.35    | 1.5     | 11 | 100 | 22                | 12 | 9    |
| M16 | 0.35    | 1.5     | 12 | 100 | 22                | 12 | 9    |
| M16 | –       | 2       | 12 | 110 | 32                | 12 | 9    |
| M18 | 0.35    | 1.5     | 14 | 110 | 25                | 14 | 11   |
| M18 | –       | 2       | 14 | 125 | 34                | 14 | 11   |
| M20 | 0.35    | 1.5     | 16 | 125 | 25                | 15 | 12   |
| M20 | –       | 2       | 16 | 140 | 34                | 15 | 12   |
| M22 | 0.35    | 1.5     | 18 | 125 | 25                | 17 | 14.5 |
| M22 | –       | 2       | 18 | 140 | 34                | 17 | 14.5 |
| M24 | 0.35    | 2       | 18 | 140 | 28                | 17 | 14.5 |
| M27 | 0.35    | 2       | 20 | 140 | 28                | 19 | 16   |
| M30 | 0.35    | 2       | 22 | 150 | 28                | 21 | 18   |
| M30 | –       | 3       | 22 | 180 | 45                | 21 | 18   |

\* Maximum